

Electromagnetic type BTU Meter 200



Modelcode : FLOEMS-200P3B1C4K1E2T1J1L1D1F1F2U1

Size	: 8" DN200
Service fluid	: Water (no corrosion)
Water temperature range	: 5 degC to 25 degC
Electrode material	: SS316L
Lining material	: Rubber
Accuracy	: 0.5% F.S.
Output	: 4-20mA
Communication	: RS485 Modbus
Process Max. Pressure	: 10 bars
Power supply	: 220V AC 50Hz
Integral type	
Meter body material	: carbon steel
Process connection	: Flange to PN16

With two Pt1000 temperature sensors

With our factory calibration report

Electromagnetic type BTU Meter 250



Modelcode : FLOEMS-250P3B1C4K1E2T1J1L1D1F1F2U1

Size	: 10" DN250
Service fluid	: Water (no corrosion)
Water temperature range	: 5 degC to 25 degC
Electrode material	: SS316L
Lining material	: Rubber
Accuracy	: 0.5% F.S.
Output	: 4-20mA
Communication	: RS485 Modbus
Process Max. Pressure	: 10 bars
Power supply	: 220V AC 50Hz
Integral type	
Meter body material	: carbon steel
Process connection	: Flange to PN16

With two Pt1000 temperature sensors

With our factory calibration report

Project Reference :

- **Blok B Tanah Abang**
- **Pabrik Goodyear Indonesia**
- **PT.Timah International Investment**